Husqvarna

HUSQVARNA 135R

Versatile brushcutter, perfect for homeowners. Easy starting with Smart Start® recoil system and fuel pump. The X-Torq® engine provides raw power and excellent fuel economy. Comes with double harness, easy loading semi automatic trimmer head and grass knife.

Standard double harness
Standard harness for lighter brushcutters.

High torque bevel gear
Bevel gear designed with high torque and the cutting equipment parallel to the ground for best cutting performance.

Adjustable handle bar
Adjustable and ergonomically designed handlebar for best comfort.

X-Torq® engine
The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.

Easy starting
Air purge for very easy starting.

Auto return stop switch
When the machine is turned off, the stop button automatically returns to start position for trouble free starting.

Additional features

Combi-guard
The cutting attachment combi-guard can be used with either a grass blade or a trimmer head.

Tap 'N Go™ trimmer head
Twin line cutting system with Tap 'N Go™ for quick line feed.

Comfortable handle
Comfortable handle design.

Technical data

Engine specification

Cylinder displacement	2.1 cu.inch / 34.6 cm^3
Cylinder bore	1.5 inch / 38 mm
Cylinder stroke	1.2 inch / 30.5 mm
Power output	1.9 hp / 1.4 kW
Maximum power speed	8400 rpm
Fuel tank volume	20.3 fl oz / 0.6 lit
Fuel consumption	435 g/kWh

Technical data

Ignition module air gap	0.01 " / 0.3 mm
Idling speed	2900 rpm
Spark plug	Champion RCJ6Y
Electrode gap	0 " / 0.5 mm
Clutch engagement speed	3800 rpm (±120 rpm)
Vibration & noise data	
Equivalent vibration level (ahv, eq) left / right handle	2.9/2.5 m/s^2
Sound pressure level at operators ear	98 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Transmission data	
Gear ratio	1:1.4
Drive gear angle	35 °
Equipment	
OEM Trimmer head	T35 M12
OEM Grass blade	Multi 300-3
OEM Harness	Standard double harness
Overall dimensions	
Weight (excl. cutting equipment)	15 lbs / 6.8 kg
Tube length	58.4 inch / 1483 mm
Tube diameter	1.1 " / 28 mm
Logistical data	
Packaging size, LxWxH1xH2	72.2x12.8x12.2x4.5 inch / 1834x324x310x114 mm

Standard equipment

537 33 16-01 - Combi guards

578 44 45-01 - Grass knife 3-tooth

503 89 01-02 - Support Cups

537 21 63-01 - Harness Standard

Accessories