



## HUSQVARNA R 216

Efficient Rider with 94cm Combi cutting deck, offering first-class BioClip® and rear ejection cutting. Suitable for homeowners who require high efficiency, ease of use, superior manoeuvrability and a truly enjoyable ride. The articulated steering system and front-mounted cutting deck means intuitive operation, excellent mowing accessibility and a great overview of your working area. Pedal-operated hydrostatic transmission, easy-access controls and automatic blade engagement, makes mowing a pleasure. The cutting deck is easily tilted up into the service position for easy cleaning after mowing. This Rider can do so much more than cutting your lawn. Thanks to attachments such as a trailer, sweeper and spreader, it can maintain your garden all year round. Note - Complete with Combi 94 Deck (94cm)



### Articulated steering

The unique articulated steering system allows the rear pair of wheels to swing in underneath the machine. The result is superior manoeuvrability with a minimum turning radius at full lock.



### Front-mounted cutting deck

Front-mounted cutting deck for excellent accessibility into corners and under bushes, park benches etc.



### Optional Combi cutting deck

This Rider is fitted with a 94 cm Combi cutting deck for efficient BioClip® and rear ejection cutting.



### Service position

Service position on the cutting deck facilitates cleaning and servicing.



### External fuel cap

Thanks to the external fuel cap, you don't have to open the engine hood when taking on more fuel. The extra wide fuel tank opening makes refueling even easier.



### Pedal-operated hydrostatic transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.

## Additional features

### Comfortable driver's position

With a Rider you get safety, stability and traction on both flat grounds and hillsides. The Rider's low centre of gravity contributes to extra traction as well as a comfortable "sit-in" feeling for the user.

### Easy-access controls

Controls are easily accessible and designed for optimum user comfort.

### Easy-access cutting height lever

The cutting height lever is easy to reach from the driver's seat, making it possible to do cutting height changes while mowing.

### Rear ejection

### Versatile usage

A wide range of cutting decks and attachments will make your front mower exceptionally versatile, all year round.

### Automatic blade engagement

The blades are engaged automatically, when you lower the cutting deck.

### BioClip®

BioClip® (mulching) provides excellent cutting results on frequently cut areas. The grass is cut into fine pieces that quickly decompose and return to the lawn as natural fertiliser.

### Four large wheels

### Additional features

The rear ejection cutting mode provides highly-effective cutting performance on areas that are cut less frequently.

#### Engine behind driver

Thanks to the rear-mounted engine, you get a better overview of the mowing and less noise and emissions in the driver's area.

#### Easy-access service points

The tilting hood and easy-access servicing points make maintenance and servicing easy.

#### Pivoting rear axle

The rear axle is pivoting to get maximum traction on the drive wheels and a smooth ride on uneven surfaces.

#### Bottle holder

Convenient bottle holder for refreshments.

Large wheels both front and back provide optimal riding comfort, great accessibility and less risk of damaging delicate surfaces.

#### Adjustable pitch angle

Possible to fine-tune the cutting deck position, to ensure perfect cutting results at all times.

#### Transparent fuel tank

Large, transparent fuel tank makes it easy to check the fuel level.

#### Storage compartment

The open left-hand storage is easy to access while mowing.

## Technical data

### Engine

Engine manufacturer	Briggs & Stratton
Engine name	Intek
Engine type	4155
Net power at preset rpm	9.6 kW @ 2900 rpm
Cylinder displacement	30.51 cu.inch / 500 cm <sup>3</sup>
Cylinders	1
Engine cooling	Air
Generator	3 A
Battery	12 V 24 Ah
Fuel Type	Gasoline
Fuel tank volume	3.2 gal. / 12 lit
Engine lubrication type	Pressure
Oil type	SAE10W30
Oil capacity	50.7 fl oz / 1.5 lit
Oil filter	Yes

### Drive system

Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Transmission model	K46
Drive method	Pedal-operated
Speed forward, min-max	0-5.6 mph / 0-9 km/h
Speed reverse, min-max	0-5.6 mph / 0-9 km/h
Safety limit slopes	10 °

### Cutting deck

Uncut circle <sup>1</sup>	11.8 inch / 30 cm
Cutting width, Min-Max	37-40.6 inch / 94-103 cm
Optional cutting decks	Combi 94, Combi 103
Cutting deck type	Combi
Cutting deck material	Steel
Cutting methods	BioClip®/Rear discharge
Cutting height, min-max	1 - 3 inch / 25 - 75 mm
Cutting height steps	10 pcs
Blade engagement	Automatic

**Technical data**

Blades	3
Powder-coated cutting deck	Yes

**Other**

Seat material	Vinyl
Seat back height	Medium
Foldable seat	Yes

**Dimensions**

Tyre dimensions, front	170/60-8
Tyre dimensions, rear	170/60-8
Wheelbase	34.9 " / 88.7 cm
Ground clearance	4.1 inch / 105 mm
Base machine, length	74.8 inch / 190 cm
Base machine, width	35 inch / 89 cm
Base machine, height	42.1 inch / 107 cm
Weight	434.3 lbs / 197 kg
Gross weight towed <sup>2</sup>	242.5 lbs / 110 kg

**Sound and noise data**

Sound pressure level at operators ear	85 dB(A)
Sound power level, measured	99 dB(A)
Sound power level, guaranteed (LWA)	100 dB(A)

**Vibrations**

Vibration level steering wheel	2.5 m/s <sup>2</sup>
Vibration level seat	0.7 m/s <sup>2</sup>

**Logistics**

Packaging Type	Wood crate
Packaging size, LxWxH	90.94x44.09x38.58 inch / 2310x1120x980 mm
Packaging volume	89.7 cu.feet / 2.54 m <sup>3</sup>
Gross weight	141.09 lbs / 64 kg
Packaging, gross weight	114.64 lbs / 52 kg
Packaged weight	575.4 lbs / 261 kg
Pallet Size, LxWxH	89.37x40.94x6.1inch / 2310x1120x155mm
Quantity per pallet	1 pcs
Quantity per trailer	24 pcs

**Accessories**