



HUSQVARNA 125B

Efficient hand held blower that combines high blowing power with user friendliness. Perfect for home owners. Well balanced and easy to manoeuvre thanks to the in-line air out let.



In line outlet

The fan housing is designed so that the air stream is in line with the handle. This makes the machine very easy to manoeuvre.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



Cruise control

Fan speed can be set for easier handling.



Adjustable tube length

The blowing tube length is adjustable for best performance.



Intuitive controls

The controls are well gathered and easy to access.



Easy starting

Air purge for very easy starting.

Technical data

Engine specification

Cylinder displacement	1.7 cu.inch / 28 cm ³
Cylinder bore	1.4 inch / 35 mm
Cylinder stroke	1.1 inch / 28.7 mm
Power output	1.1 hp / 0.8 kW
Maximum power speed	8000 rpm
Fuel tank volume	16.91 fl oz / 0.5 lit
Fuel consumption	575 g/kWh
Spark plug	Champion RCJ6Y

Article data

Air flow in housing	470 cfm / 13.31 m ³ /min
Air flow in pipe	425 cfm / 12.03 m ³ /min
Air speed	170 mph / 76 m/s
Air speed (round nozzle)	130 mph / 58.12 m/s
Air speed (flat nozzle)	170 mph / 76 m/s

Vibration & noise data

Technical data

Equivalent vibration level (ahv, eq) handle	11.1 m/s ²
Sound pressure level at operators ear	92 dB(A)
Sound power level, guaranteed (LWA)	107 dB(A)
Sound pressure (15m)	70 dB(A)

Equipment

OEM Harness	--
OEM Nozzle type	Round+ Flat

Overall dimensions

Weight	9.4 lbs / 4.26 kg
--------	-------------------

Logistical Data

Weight incl. packaging	13.23 lbs / 6 kg
Packaging size, LxWxH	16.5x8.5x16.5 inch / 419x216x419 mm
Pallet quantity	45
Products per 20ft container	720 pcs
Products per 40ft HC container	1620 pcs

Accessories