



HUSQVARNA PZ 34

The Husqvarna PZ Series represents the latest in high performance drive systems and operator interfaces. Combined with high productivity cutting deck designs, these mowers deliver premium cut quality and clipping dispersal at higher ground speeds. Careful consideration of components and design not only provide extended durability but unprecedented ease of service access. *Price includes 153 cm/60" deck. Can also be fitted with 183 cm/72" fabricated side discharge cutting deck at additional cost.



Zero-turn steering system
Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axis. The result is increased productivity.



Hands-free deck lift
The robust, pedal-operated deck lift system allows quick, hands-free operation.



Flat-free casters
Durable steel front caster yokes feature heavy-duty tapered roller bearings and flat-free tires.



Removable foot pan
Removable foot pan for easy access to deck belt pulleys, spindles and clean-up.



Convenient operator interface
The control panel is ergonomic in design and within easy reach of operator.



Vibration-isolated platform
Rubber isolators set your hands, body and feet apart from the frame, which means less fatigue during operation.

Additional features

Hour meter with service minder

Indicates when it's time to service your mower.

13 Bushel Collection System

Increase productivity and versatility with a 13 bushel triple bag collection system. Unique design removes or installs in a matter of minutes.

Hydro drive system

The standard drive system features Hydro-Gear pumps and Parker wheel motors. The 7" cooling fans and oversized 1.5 gallon oil capacity extend service life and offer smooth performance.

Roll Over Protection System (ROPS)

The practical foldable ROPS protects the user and can be lowered in areas with low-hanging branches.

Premium suspension seat

Deep cushions and EVC (elastomeric vibration control) provide unsurpassed comfort for the operator. Additional full suspension system gives a smoother ride on rough terrain during long working hours.

Commercial-grade Engine

The Kawasaki V-twin is an overhead valve engine with full pressure lubrication and spin-on oil filter. It combines exceptional power and torque with fuel efficiency and reduced emissions.

Easy-access service points

Oil and filter maintenance, hydraulic drive system components/adjustment, electrical system and battery are all within easy reach so you can quickly get back to being productive.

Additional features

Combi cutting deck

Combi cutting deck, an improved heavy-duty BioClip® deck that doubles as a rear ejection deck with the aid of a removable BioClip® plug. High performance deck features heavy-duty 4.5 mm (7 gauge) stamped steel construction. Performance and clipping dispersal are enhanced by the increased flow of the 152 mm (6") deep tunnel design.

Oversized chassis

2" x 3" tube chassis combined with large rear and front tyres provide superior strength and improved ride quality.

Adjustable steering levers

Steering levers are adjustable for different size operators - ergonomically angled inward for more comfort and can be adjusted to suit your particular style.

Convenient Control Panel

Convenient side mounted control panel places the choke, throttle, and ignition in one location for easy access.

Adjustable tracking

The easily accessible adjustment allows fine-tuning of straight line tracking without tools.

Optional Light Kit

Optional high powered clamp on style headlights feature simplified installation, plug directly into harnesses on 2005+ units and are functional with existing key switch.

High-performance cutting deck

The combination of 6" deck depth, high-performance blades and optimized deck baffles allows for exceptional cut quality and clipping dispersal. This gives you faster cutting speeds for increased productivity while minimizing missed grass or clumps.

Heavy-duty construction

The heart of the cutting deck is 7-gauge steel with a rolled front edge, 1-1/2" x 1/2" front and side reinforcement, and heavy-duty double-supported scalloped rollers.

Heavy-duty canister air filter

The heavy-duty canister air filter provides maximum protection for the engine in tough mowing conditions.

Rugged, hands-free deck lift

The deck lift system utilises heavy-duty components supported by maintenance-free composite bushings, for smooth function and increased durability.

Stable ride

Low centre of gravity and wide stance ensure exceptional stability and riding comfort. Wide tyres reduce grass compaction.

Large fuel capacity

11.4 gallons (Dual 5.7 gallon tanks) for up to 12 hours of mowing time. Large 3.5 inch diameter refill tube for easy refuelling.

Technical data

Engine

Engine manufacturer	Kawasaki
Engine name	FX Series
Engine type	FX921V V-Twin
Net power at preset rpm	23.1 kW @ 3600 rpm
Cylinders	2
Engine cooling	Air
Air Filter type	Heavy-Duty Canister Style
Fuel Type	Gasoline
Fuel tank volume	11 gal. / 41.6 lit
Fuel tank location	Side (Dual)
Engine lubrication type	Full pressure
Oil capacity	57.6 fl oz / 1.7 lit
Oil filter	Yes

Drive system

Transmission type	Pump/Wheel motor
Transmission manufacturer	Hydro-Gear/Parker
Pump displacement	16 cm ³
Wheel motor displacement	19 cu.inch / 311.4 cm ³
Fan-cooled pumps	Yes
Hydraulic reservoir	6 qt / 5.7 lit
Speed forward, min-max	0-12 mph / 0-19.3 km/h
Speed reverse, min-max	0-6 mph / 0-9.7 km/h

Cutting deck

Cutting deck material	Steel
Cutting height, min-max	1 - 5 inch / 25 - 127 mm

Technical data

Cutting height steps	17
Blade engagement	Electric clutch
Clutch rating	250 ft.lb / 339 Nm
Blades	3
Deck lifting system	Manual, foot activated
Powder-coated cutting deck	Yes

Other

ROPS	Yes
Flat-free front tyres	Yes
Seat type	Premium, suspension with seatbelt
Seat material	Vinyl
Seat suspension	Yes
Seat back height	High
Armrests	Yes
Hour meter	Digital with pre-programmed service intervals
Cup holder	Yes

Dimensions

Tyre size, front	13x6.5-6"
Tyre size, rear	24x12-12"
Wheelbase	55 " / 139.7 cm
Base machine, length	82.5 inch / 209.6 cm
Base machine, height (ROPS down)	47.5 inch / 120.7 cm
Base machine, height (ROPS up)	72 inch / 182.9 cm
Weight	931 lbs / 422.3 kg

Logistics

Packaging Type	Wood and cardboard treated and bark-free
Packaging size, LxWxH	85.5x68.5x53 inch / 2171.7x1739.9x1346.2 mm
Packaging volume	179.6 cu.feet / 5.1 m ³
Packaged weight	1090 lbs / 494.4 kg
Pallet Size, LxWxH	85.5x68.5x53inch / 2171.7x1739.9x1346.2mm
Quantity per pallet	1 pcs
Quantity per container	20ft:0 40ft:0 40HC:23pcs

Accessories